



FOUNDATION ASSOCIATES ENGINEERING PTE LTD

5, Tuas Avenue 1, Singapore 639490  
Tel: (65) 6863 1633 Fax: (65) 6863 1455  
Email: fnapl@singnet.com.sg Website: http://www.fnapl.com



CESCO

AUSTRALIA LIMITED

38 Goodman Place, Mararie QLD 4172  
P.O. Box 7138, Hemmant QLD 4174  
www.cescoaustralia.com  
Tel: +617 3908 6088 Fax: +617 3390 6898

A member of the ZICOM GROUP

## FAV 416L / 416L HD HYDRAULIC VIBRATORY HAMMER



Eccentric moment	2,200 in-lbs (25.4 kgm)
Frequency	1860 vpm (1860 vpm)
Centrifugal force	110 tons (972 kN)
Amplitude (free hanging)	0.98 in (25 mm)
Max line pull for extracting	40 US ton (355 kN)
Weight (no clamps & hoses)	7,400 lbs (3360 kg)
Non-vibrating weight	2,900 lbs (1315 kg)
Height (without clamp)	71.6 in (1820 mm)
Length (inclu. hose chute)	111 in (2830 mm)
Width	17 in (430 mm)
Throat width	14 in (355 mm)
Hydraulic hose length	100 ft (30 m)
Hydraulic hose weight (w/o oil)	850 lbs (385 kg)

## FAV 335, 375, 400 POWERPACK



### FAV 375

Engine: John Deere 6125 Brand New  
Max. Drive Flow: 390 litres / min  
Max. Drive Pressure: 320 bar  
Power: 375 HP  
Operating Speed: 2100 rpm

- Conceal exhaust silencer and 4 lifting eyes
- Stainless steel latches & hinges Operating Speed: 2100 rpm
- Noise reduction panels
- External fuel & hydraulic tank inspection allocations
- 3600 (L) x 1500 (B) x 1800 (H)
- 5 Ton (approx.)

Optional: Different make of new and refurbished diesel engines are available upon requests