

The Weight\$aver





STANDARD	WEIGHTON	VED MIVED
SIANDARD	WEIGHINA	VER WILLER

- ✓ Hardox light weight Barrel
- ✓ 8mm reinforced dished end
- ✓ Frame including, chute rack, swivel chute, feed chute
- ✓ Oil tank, cooler and hydraulic pump.
- Gearbox ZF Ecomix II CML 10 with hydraulic pump
- Single step and grab handle Driver side
- ✓ LED work light and tail lights
- √ NO ladder or platform
- ✓ Plastic guards (Rear only)
- ✓ 2 x Ally frame poly lined extension chutes, 1 x Ally framed poly lined ½ placement chute
- ✓ Remote controls with transit mode
- Steel grease able trunnion rollers with side mounted safety guards
- ✓ Water meter and slump gauge
- ✓ Double acting hydraulic ram with safety valve
- ✓ 200L pressurised water system
- ✓ Painted in polyurethane paint one colour barrel one colour frame NO company LOGO
- Removable inlet bridge

OPTIONAL EXTRAS

- ✓ 2nd Barrel colour Company Logo and livery
- ✓ ASL ladder and Platform
- ✓ Reverse camera
- ✓ Clear coat on barrel
- Single step both sides
- Double step both sides
- ✓ Triple step both sides
- Full ally chutes
- ✓ Swivel feed chute Vibrator
- ✓ Chute raise and lower switch at rear

Advances in design or improvements in materials are incorporated without delay, consequently we reserve the right to alter details given on this specification sheet without notice. Centre of gravity may vary depending on selected options.



The Weight\$aver



Dimensions		6.5 m ³		7.6 m ³	8.0 m ³	9.0m ³		
Total Barrel Volume		10.1 m ³		12.2 m ³	13.1 m³	13.8m³		
Mixing Capacity to AS1379 - 2007		6.5 m ³		7.6 m ³	8.0 m ³	9.0m ³		
Height to Feed Chute (A)		2,410 mm		2,480 mm	2,530 mm	2,600 mm		
Height Overall (B)		2,540 mm		2,620 mm	2,680 mm	2,720 mm		
Nominal Length on Truck Chassis (C)		4,900 mm		5,100 mm	5,350 mm	5,840 mm		
Nominal Length Overall (D)		5,400 mm		5,600 mm	5,850 mm	6,370 mm		
Centre of Gravity – estimated (E)		2,300 mm		2,620 mm	2,750 mm	2,998 mm		
Height of Centre of Gravity (approx.) (F)		947 mm		936 mm	966 mm	1010 mm		
Barrel Specification: Width								
Dished End 8	8mm High Tensile Reinforced		Width over Mudguards		2,460 mm			
Back Cone 3	3mm Hardox High Tensile Steel		Outside Chassis Width		860 mm			
Nose Cone 3	3mm Hardox High Tensile Stee		eel Standard Chassis Rails		100 x 76 x 5 RHS			
Mix Blades 3mm Hardox High Tensile Steel								
Cesco Australia Limited								
Brisbane: Head Office								
Mixer S	ervice Centre:	38 Goodman Place Murarrie Qld 4172			Ph: 07 3908 6088 F: 07 3390 6898			
Melbourne: Mixer S	ervice Centre:	76-78 Hallam South Road Hallam Vic 3903			Ph: 03 9796 4977 F: 03 9796 4811			

Note: Specifications and mixer layout are for references only and subject to actual applications and components availability.